

User's Guide

IEEE 802.11n Wireless PCI Adapter

FCC Certifications



Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

IMPORTANT NOTE:

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

IEEE 802.11b/g or 802.11n operation of this product in the U.S.A. is firmware-limited to channels 1 through 11.

CE Mark Warning



This equipment complies with the requirements relating to electromagnetic compatibility, EN 55022 Class B for ITE, the essential protection requirement of Council Directive 89/336/EEC on the approximation of the laws of the Member States relating to electromagnetic compatibility.

Company has an on-going policy of upgrading its products and it may be possible that information in this document is not up-to-date. Please check with your local distributors for the latest information. No part of this document can be copied or reproduced in any form without written consent from the company.

Trademarks:

All trade names and trademarks are the properties of their respective companies.

Copyright © 2007, All Rights Reserved.

TABLE OF CONTENTS

OVERVIEW	4
UNPACKING INFORMATION	4
INTRODUCTION TO THE IEEE 802.11N WIRELESS PCI ADAPTER	4
KEY FEATURES	5
INSTALLATION GUIDE	5
SOFTWARE INSTALLATION	5
MANAGEMENT GUIDE	8
MAKING A BASIC NETWORK CONNECTION	8
Select a configuration tool	8
To connect with Microsoft Zero Configuration tool	8
To connect with 802.11n Wireless LAN Utility	10
INTRODUCTION TO THE 802.11N WIRELESS LAN UTILITY	11
Interfaces	11
Information	12
Profile	13
Network	17
Advanced	18
Statistics	19
WMM	20
WPS	20
APPENDIX	22
INTRODUCTION TO THE CONFIGURATION UTILITY FOR VISTA USERS	22
Profile	22
Link Status	24
Site Survey	25
Statistics	26
AP MODE MANAGEMENT GUIDE	30
Config	30
Access Control	33
MAC Table	34
Event Log	34
Statistics	35
PRODUCT SPECIFICATION	36

Overview

Thank you for purchasing this product. Read this chapter to know about your IEEE 802.11n Wireless PCI Adapter.


Unpacking Information

Before getting started, please verify that your package includes the following items:

1. IEEE 802.11n Wireless PCI Adapter.
2. Three detachable antennae.
3. One Utility/ Manual CD.

Introduction to the IEEE 802.11n Wireless PCI Adapter

The IEEE 802.11n Wireless PCI adapter provides users to launch IEEE 802.11n wireless network at 300 Mbps in the 2.4GHz band, which is also compatible with IEEE 802.11b/g wireless devices at 11/54 Mbps. You can configure this adapter with Ad-hoc mode to connect to other 2.4GHz wireless computers, or with Infrastructure mode to connect to a wireless AP or router for accessing to Internet. This adapter includes a convenient Utility for scanning available networks and saving preferred networks that users usually connected with. Security encryption can also be configured by this Utility.



Key Features

- Complies with IEEE 802.11n/b/g wireless standards
- 2.4GHz Frequency band, MIMO 2T3R
- Complies with PCI 2.3
- High Speed transfer data rate up to 300 Mbps
- Supports auto-installation.
- Supports driver for Windows 2000, XP 32/64, and Vista 32/64
- Supports QoS: WMM, WMM-PS
- Supports wireless data encryption with 64/128-bit WEP, WPA, WPA2
- Supports Multiple BSSID

Installation Guide

Software Installation

Note: The following driver installation guide uses Windows XP as the presumed operation system. The procedures and screens in Windows 2000 and Vista are familiar with Windows XP.

1. Insert this product to your computer. The system finds the newly installed device automatically. Click **Cancel** to close this window.




2. Insert the CD-Rom that came with this product to your CD-Rom drive. The menu window pops up automatically. Please click the **Driver** button of this product.

Note: If the CD-Rom fails to auto-run, please click on **My Computer > your CD-Rom drive > (folder of this product) > Driver** then double-click the **Setup** icon to start this menu.


3. Select if you are going to configure your wireless network with this device or with Microsoft Zero Configuration tool.

Note: This can be changed after installing this software.




4. Select to optimize this adapter in WiFi mode or performance mode.


Note: The performance mode is only available while connecting to a TX Burst supported AP. Users that uses the AP without TX Burst please select WiFi mode (standard mode).



5. Click the **Install** button to start installing.



6. Click the **Finish** button to complete installation.




Management Guide


Read this chapter to understand the management interface of the device and how to manage the device.

Making a Basic Network Connection


Select a configuration tool


In the following instruction for making a network connection, we use the Utility we provide to configure your wireless network settings.

Note: You could use either the software we provide or Microsoft Zero Configuration tool to configure this adapter. To switch between the two configuration tools, please right click on the  icon on system tray to select.




To connect with Microsoft Zero Configuration tool


After specifying the Microsoft Zero Configuration tool to configure your wireless network, right click on the  icon on system tray. Select **View Available Wireless Networks** to specify your wireless network.




The tool shows the available wireless networks. Select your demanding network to connect with. To connect to a wireless network with more security settings, please click **Change advanced settings** to be compatible with your wireless network security settings.



To connect with 802.11n Wireless LAN Utility

We provide this Utility for users to connect to a wireless network easily. It provides more information and configuration for this adapter. As default, the Utility is started automatically upon starting your computer and connects to a connectable wireless network with best signal strength. Right click on the  icon and select **Launch Config utilities** if the Utility does not start. Please refer to the following chapters to get information regarding to the functions of this Utility.





Introduction to the 802.11n Wireless LAN Utility

Note: The Utility in Windows Vista is different from the following. For instructions on using the Utility included in Windows Vista please refer to the instruction in [Appendix](#).

Interfaces

This Utility is basically consisted of three parts:


1. Functional buttons: on top of the window. You can click each button to access each configuration window.

Note: Click  on the top right window to enable/disable wireless connection status.
Click  to show the wireless information.



2. Configuration column: Center of the Utility window. Make your changes for each function in this part.
3. Status information: bottom of the utility window. Shows the connection status and system information.

Information



Items	Information
Status	Shows the connecting status. Also shows the SSID while connecting to a valid network.
Extra Info	Display link status in use.
Channel	Display current channel in use.
Authentication	Authentication mode in use.
Encryption	Encryption type in use.
Network Type	Network type in use.
IP Address	IP address of current connection.
Sub Mask	Subnet mask of current connection.
Default Gateway	Default gateway of current connection.
Link Speed	Show current transmit rate and receive rate.
Throughput	Display transmit and receive throughput in Mbps.
Link Quality	Display connection quality based on signal strength and TX/RX packet error rate.
Signal Strength 1	Receive signal strength 1, user can choose to display as percentage or dBm format.
Signal Strength 2	Receive signal strength 2, user can choose to display as percentage or dBm format.
Signal Strength 3	Receive signal strength 3, user can choose to display as percentage or dBm format.
Noise Strength	Display noise signal strength.
HT	Display current HT status in use, containing BW, GI, MCS, SNR0, and SNR1 value.

Profile

This profile page allows users to save different wireless settings, which helps users to get access to wireless networks at home, office or other wireless network environments quickly.

To add a new profile:

1. Click the **Add** button. The add profile window pops up.
Note: you could also add a new profile quickly by selecting an available network in the **Network** function then click the **Add to Profile** button.
2. Fill in information for this profile in the system config section:

Items	Information
Profile Name	Choose a name for this profile, or use default name defined by system.
SSID	Fill in the intended SSID name or use the drop list to select from available Aps.
Power Save Mode	Choose from CAM (Constantly Awake Mode) or PSM (Power Saving Mode).
Network Type	There are two types, infrastructure and 802.11 Ad-hoc modes. Under Ad-hoc mode, you could also choose the preamble type; the available preamble type includes auto and long. In addition to that, the channel field will be available for setup in Ad-hoc mode.
RTS Threshold	For adjusting the RTS threshold number by sliding the bar or key in the value directly. The default value is 2347.
Fragment Threshold	Adjust the Fragment threshold number by sliding the bar or key in the value directly. The default value is 2346.

3. Select an encryption type and fill in the corresponding wireless network information:

Items	Information
Authentication Type	There are 7 types of authentication modes supported by Utility including open, Shared, LEAP, WPA and WPA-PSK, WPA2 and WPA2-PSK
Encryption Type	For open and shared authentication mode, the selection of encryption type are None and WEP. For WPA, WPA2, WPA-PSK and WPA2-PSK authentication mode, the encryption type supports both TKIP and AES.
802.1x	Use 802.1x to make WPA and WPA2 certification. This functions only works when connecting to a WPA and WPA2 supported device.
WPA Pre-shared Key	This is the shared secret between AP and STA. For WPA-PSK and WPA2-PSK authentication mode, this field must be filled with character longer than 8 and less than 32 length.
WEP Key	Only valid when using WEP encryption algorithm. The key must matched AP's key.

4. Specify the 802.1x information if you are using the 802.1X certification method.

Users that do not use this function or connecting to an open-wireless network please skip this part.

Items	Information
EAP method	To select an EAP method.
Tunnel Authentication	Select a Tunnel authentication mode.
Session Resumption	Select to enable this function or unmark it to disable.

ID \ PASSWORD

The screenshot shows the 'ID \ PASSWORD' tab selected in the EAP configuration window. The window title is 'Auth. \ Encry.' with a green bar indicating '8021X'. Below the title bar, there are dropdown menus for 'EAP Method >>' (set to PEAP) and 'Tunnel Authentication >>' (set to EAP-MSCHAP v2), along with an unchecked 'Session Resumption' checkbox. The 'ID \ PASSWORD' tab is highlighted in red, with 'Client Certification' and 'Server Certification' tabs visible behind it. The main area contains two sections: 'Authentication ID / Password' and 'Tunnel ID / Password'. Each section has three input fields: 'Identity >>', 'Password >>', and 'Domain Name >>'. At the bottom are 'OK' and 'Cancel' buttons.

Items	Information
Authentication ID / Password	The identity, password and domain name for server. Only "EAP-FAST" and "LEAP" authentication can be key in domain name. Blank space can be key in domain name.
Tunnel ID / Password	Identity and Password for server.

Client Certification

The screenshot shows the 'Client Certification' tab selected in the EAP configuration window. The window title is 'Auth. \ Encry.' with a green bar indicating '8021X'. Below the title bar, there are dropdown menus for 'EAP Method >>' (set to PEAP) and 'Tunnel Authentication >>' (set to EAP-MSCHAP v2), along with an unchecked 'Session Resumption' checkbox. The 'Client Certification' tab is highlighted in red, with 'ID \ PASSWORD' and 'Server Certification' tabs visible behind it. The main area contains a checkbox labeled 'Use Client certificate'. To its right is a dropdown menu showing 'wpatest2', '2003serv', and '4/9/2008'. Below this are four labels with corresponding input fields: 'Issued To >> wpatest2', 'Issued By >> 2003serv', 'Expired On >> 4/9/2008', and 'Friendly Name >>'. At the bottom are 'OK' and 'Cancel' buttons.

Items	Information
Use Client certificate	Client certificate for server authentication.

EAP Fast


Items	Information
Allow unauthenticated provision mode	Mark to enable unauthenticated provision mode.
Use protected authentication credential	Mark to use protected authentication credential.

Server Certification

Items	Information
Use Certificate chain	Mark the checkbox to enable using certification chain.
Allow intimidate certificates	Mark to allow intimidates certification
Server name	Enter an authentication sever root.

Network

This network lists the available wireless networks. The Utility connects to a wireless network with best signal strength automatically. You can change the connecting network by clicking on the network name and click the **Connect** button. To see detail information of each network, please double click on each item to pop up the information window.



Items	Information
SSID, Channel and Signal buttons	Click each button to sort the listing networks by SSID, channel and Signal strength.
Show dBm	Mark the checkbox to show the signal strength in dBm.
Rescan	To rescan available wireless networks.
Connect	Click this button to connect to a designated network.
Add to Profile	Click this button to add a network to profile after selecting a network.

Advanced

This page provides advanced configurations to this adapter. Please refer to the following chart for definitions of each item.

Wireless mode >> 802.11 B/G/N mix

☐ Enable CCX (Cisco Compatible eXtensions)

☐ Turn on CCKM

☐ Enable Radio Measurements

☐ Non-Serving Channel Measurements limit 250 ms (0-2000)

☐ Enable TX Burst

☐ Enable TCP Window Size

☐ Fast Roaming at -70 dBm

☐ Show Authentication Status Dialog

Select Your Country Region Code

11 B/G >> 0: CH1-11

Apply

Items	Information
Wireless mode	Click the drop list to select a wireless mode.
Enable TX Burst	Select to enable connecting to a TX Burst supported device.
Enable TCP Window Size	Mark the checkbox to enable TCP window size, which help enhance throughput.
Fast Roaming at __ dBm	Mark the checkbox to enable fast roaming. Specify the transmit power for fast roaming.
Show Authentication Status Dialog	Mark the checkbox to show "Authentication Status Dialog" while connecting to an AP with authentication. Authentication Status Dialog displays the process about 802.1x authentication.
Enable CCX (Cisco Compatible extensions)	Select to enable CCX. This function can only be applied when connecting to a Cisco compatible device.

Statistics

Statistics page displays the detail counter information based on 802.11 MIB counters. This page translates the MIB counters into a format easier for user to understand.

Transmit	Receive
Frames Transmitted Successfully	= 1432
Frames Retransmitted Successfully	= 4
Frames Fail To Receive ACK After All Retries	= 0
RTS Frames Successfully Receive CTS	= 0
RTS Frames Fail To Receive CTS	= 0
Reset Counter	

Items	Information
Use Client certificate	Client certificate for server authentication.
Frames Transmitted Successfully	Frames successfully sent.
Frames Retransmitted Successfully	Successfully retransmitted frames numbers
Frames Fail To Receive ACK After All Retries	Frames failed transmit after hitting retry limit
RTS Frames Successfully Receive CTS	Successfully receive CTS after sending RTS frame.
RTS Frames Fail To Receive CTS	Failed to receive CTS after sending RTS
Restart Counter	Reset counters to zero

Transmit	Receive
Frames Received Successfully	= 3153
Frames Received With CRC Error	= 201964
Frames Dropped Due To Out-of-Resource	= 0
Duplicate Frames Received	= 0
Reset Counter	

Items	Information
Use Client certificate	Client certificate for server authentication.
Frames Received Successfully	Frames received successfully
Frames Received With CRC Error	Frames received with CRC error
Frames Dropped Due To Out-of-Resource	Frames dropped due to resource issue
Duplicate Frames Received	Duplicate received frames.

WMM

This page allows users to activate the WMM function for this device. Please note that this function only works while connecting to a WMM compatible device.

WMM Setup Status

WMM >> Enabled
Power Save >> Disabled
Direct Link >> Disabled

☒ WMM Enable

☐ WMM - Power Save Enable

☐ AC_BK
☐ AC_BE
☐ AC_VI
☐ AC_VO

☐ Direct Link Setup Enable

MAC Address >>
Timeout Value >>

60

sec

Apply

Tear Down

Items	Information
Use Client certificate	Client certificate for server authentication.
WMM Enable	Enable Wi-Fi Multi-Media.
WMM - Power Save Enable	Enable WMM Power Save. Please enable WMM before configuring this function.
Direct Link Setup Enable	Enable DLS (Direct Link Setup). Please enable WMM before configuring this function.

WPS

WPS Configuration: The primary goal of Wi-Fi Protected Setup (Wi-Fi Simple Configuration) is to simplify the security setup and management of Wi-Fi networks. This adapter supports the configuration setup using PIN configuration method or PBC configuration method through an internal or external Registrar.

WPS AP List

ID : Unknown	AP1-WPS	00-10-18-90-2E-27	1	
ID : Unknown	Ubicom_Sample	00-0C-43-28-60-20	1	
ID : Unknown	arvint-2860AP	00-0C-43-28-60-60	3	
ID : Unknown	default	00-18-02-4A-0A-6B	6	

WPS Profile List

PIN

WPS Associate IE

PBC

WPS Probe IE

Progress >> 0%

WPS status is disconnected

Rescan

Information

Pin Code

26460208

Config Mode

Enrollee

Detail

Connect

Rotate

Disconnect

Delete

Items	Information
Use Client certificate	Client certificate for server authentication.
WPS AP List	Display the information of surrounding APs with WPS IE from last scan result. List information includes SSID, BSSID, Channel, ID (Device Password ID), and Security-Enabled.
Rescan	Click to rescan the wireless networks.
Information	Display the information about WPS IE on the selected network. List information include Authentication Type, Encryption Type, Config Methods, Device Password ID, Selected Registrar, State, Version, AP Setup Locked, UUID-E and RF Bands.
PIN Code	8-digit numbers. It is required to enter PIN Code into Registrar using PIN method. Each Network card has only one PIN Code of Enrollee.
Config Mode	Enrollee or an external Registrar.
Table of Credentials	Display all of credentials got from the Registrar. List information includes SSID, MAC Address, Authentication and Encryption Type. If STA Enrollee, credentials are created as soon as each WPS success. If STA Registrar, Utility creates a new credential with WPA2-PSK/AES/64Hex-Key and doesn't change until next switching to STA Registrar.
Detail	Information about Security and Key in the credential.
Connect	Command to connect to the selected network inside credentials.
Rotate	Command connect to the next network inside credentials
Disconnect	Stop WPS action and disconnect this active link. And then select the last profile at the Profile Page of Utility if exist. If there is an empty profile page, the driver will select any non-security AP.
Delete	Delete an existing credential. And then select the next credential if exist. If there is an empty credential, the driver will select any non-security AP.
PIN	Start to add to Registrar using PIN configuration method
PBC	Start to add to AP using PBC configuration method.
WPS associate IE	Send the association request with WPS IE during WPS setup. It is optional for STA.
WPS probe IE	Send the probe request with WPS IE during WPS setup. It is optional for STA.
Progress Bar	Display rate of progress from Start to Connected status
Status Bar	Display currently WPS Status

Note: When you click PIN or PBC, please don't do any rescan within two-minute connection. If you want to abort this setup within the interval, restart PIN/PBC or click Disconnect to stop WPS action.


Appendix

Introduction to the configuration utility for Vista Users

This utility helps Vista users to configure the wireless network. Please refer to the following sections for introduction.

Profile

This profile page allows users to save different wireless settings, which helps users to get access to wireless networks at home, office or other wireless network environment quickly.



Profile List

Profile Name	SSID	Channel	Authentication	Encryption	Network Ty...
PROF1	241	Auto	WPA-PSK	TKIP	Infrastructure

Add Delete Edit Activate

To add a new profile:

1. Click the **Add** button. The add profile window pops up.

Note: you could also add a new profile quickly by selecting an available network in the **Site Survey** function then click the **Add to Profile** button.


2. Fill in the information of this wireless network and its relative security settings. Please note that the information should be corresponding to the wireless network you are connecting to.



Items	Information
Deleting profile	Click the Delete button to delete the selected profile.
Editing profile	Click the Edit button to pop up the profile-setting page for users to edit the existing profile.
Activating profile	Click the Activate button to activate the selected profile.

Link Status

This Link status shows the information about the connecting. Please refer to the following chart for definition.



Items	Information
Status	Display current connection status.
Extra Info	Display link status and current channel in use.
Link Speed	Display current transmitting and receiving rates
Throughput	Display transmitting and receiving throughputs.
Link Quality	Display connecting quality based on signal strength and TX/RX packet error rate.
Signal Strength	Display receiving signal strength either in percentage or dBm format
Noise Level	Display noise signal strength.

Site Survey

This page shows the available wireless networks within the coverage of this network adapter. You could check the status of wireless network around your computer or add a network into your profile.

[illegible]

Items	Information
SSID	Name of the network.
BSSID	AP MAC address or random numbers generated for IBSS.
Phy Type	Phy Type of the network.
Signal	Signal strength of the network.
Channel	The channel in use.
Encryption	Encryption algorithm. The supported algorithms are WEP, TKIP, AES, and Not Use.
Authentication	Authentication mode. The supported modes are Unknown, WPA-PSK, WPA2-PSK, WPA and WPA2.
Network Type	Infrastructure or Ad-Hoc.
Rescan	Click the rescan button to perform re-scanning.
Add to profile	Select a network then push the add-to-profile button to bring up the profile-setting to add a wireless network profile.

Statistics

This page provides the statistics about the connection of this adapter.

The screenshot shows a window with two sections: 'Transmit Statistics' and 'Receive Statistics'. Each section contains a list of statistics with their corresponding values. A 'Reset Counter' button is located at the bottom right of the window.

Transmit Statistics		
Frames Transmitted Successfully	=	353
Frames Transmitted Successfully After Retry(s)	=	20
Frames Fail To Receive ACK After All Retries	=	2
RTS Frames Successfully Receive CTS	=	0
RTS Frames Fail To Receive CTS	=	0

Receive Statistics		
Frames Received Successfully	=	221
Frames Received With CRC Error	=	0
Frames Dropped Due To Out-of-Resource	=	0
Duplicate Frames Received	=	4

Reset Counter

Items	Information
Frames Transmitted Successfully	Frames sent successfully
Frames Transmitted Successfully After Retry	Frames sent successfully with retry
Frames Fail To Receive ACK After All Retries	Frames transmitted failed after hitting the retrying limit
RTS Frames Successfully Receive CTS	CTS frames received successfully after sending RTS frames
RTS Frames Fail To Receive CTS	The missing CTS frames after sending RTS frames
Frames Received Successfully	Frames received successfully
Frames Received With CRC Error	Frames received with CRC error
Frames Dropped Due To Out-of-Resource	Frames dropped due to insufficient resource
Duplicate Frames Received	Duplicate frames received

WPS Configuration

This page provides users to connect this adapter to a WPS (Wi-Fi Protected Setup) AP. Those available WPS supported AP are listed on the upper column. Select the AP that you want to connect to and click the **Connect** button to activate.

WPS Associate IE:

If the "WPS Associate IE" option is checked, station sends a association request with WPS IE during WPS setup.

WPS Probe IE:

If the "WPS Probe IE" option is checked, station probes a request with WPS IE during WPS setup.

SSID	BSSID	Channel	ID	Authentic...	Encryption
2860AP	00-0C-43-28-60-31	11		Unknown	None
WPSAP	00-0C-43-28-60-60	6		WPA-PSK	TKIP
ClaudeWpsAP	00-14-85-E3-D7-8B	1		WPA-PSK	TKIP

Rescan

WPS Information

Pin Code
66851882

SSID	MAC Address	Authentication	Encryption
✓ 2860AP	00-0C-43-28-60-31	OPEN	NONE

Detail

Connect

Rotate

Disconnect

Delete

PIN

WPS Associate IE

PBC

WPS Probe IE

WPS status is connected successfully - RT2860AP_Baron

Re-scanning:

Click the **Rescan** button to perform the re-scanning.

WPS AP Information:

Click the **WPS information** button to bring up the WPS capable AP information dialog window. The window shows the information including:

Authentication Type:

There are three types of supported authentication modes including Open, Shared, WPA-PSK and WPA modes.

Encryption Type:

For Open and Shared authentication modes, the available encryption types are None and WEP. For WPA, WPA2, WPA-PSK and WPA2-PSK authentication modes, the available encryption types are TKIP and AES.

Config Methods:

This attribute contains the config methods supported and enabled by the selected Registrar.

Device Password ID:

Device Password ID indicates the method or identifies the specific password that the selected Registrar intends to use.

Selected Registrar:

Selected Registrar indicates if the user has recently activated a Registrar to add an Enrollee.

State:

This attribute is used to indicate the current configuration state. This attribute is either "Un-configured" or "Configured".

Version:

This attribute is the specified WPS version.

AP Setup Locked:

AP Setup Locked indicates if AP has entered a setup locked state.

UUID-E:

UUID-E is universally unique identifier (UUID) generated by the Enrollee.

RF Bands:

RF Bands indicate the available RF bands.



The image shows a Windows-style dialog box titled "WPS Information". It contains a list of configuration attributes and their values, each in a separate row with a label on the left and a text field on the right. The attributes and values are: Authentication (WPA-PSK), Encryption (TKIP), Config Methods (0x008A), Device Password ID (empty), Selected Registrar (empty), State (Unconfigured), Version (1.0), AP Setup Locked (empty), UUID-E (30313233303031336433366264353766), and RF Bands (empty). An "OK" button is located at the bottom right of the dialog.

Attribute	Value
Authentication	WPA-PSK
Encryption	TKIP
Config Methods	0x008A
Device Password ID	
Selected Registrar	
State	Unconfigured
Version	1.0
AP Setup Locked	
UUID-E	30313233303031336433366264353766
RF Bands	

Configure WPS profiles:

The user can configure WPS profiles with either PIN method or PBC method.

PIN Method:

Step 1: The Registrar enters the pin code generated by station.

Step 2: Push the "PIN" button.

PBC Method:

Push the "PBC" button within 2 second while the Registrar pushes the button.

Manage WPS profiles:

The received WPS profiles are listed in the lower frame, and the listed WPS profile attributes are SSID, MAC address, authentication type, and encryption type.

WPS profile detail information:

Selecting a profile then pushing the "Detail" button brings up the WPS profile.

A screenshot of a Windows-style dialog box titled "WPS Profile Detail". The dialog box has a blue title bar with a close button (X) in the top right corner. The main area is light gray and contains several text input fields. The first row has "Authentication Type:" followed by a text box containing "WPA-PSK" and "Encryption Type:" followed by a text box containing "TKIP". The second row has "Key Length:" followed by a text box containing "8" and "Key Index:" followed by an empty text box. The third row has "Key Material:" followed by a wide text box containing "12345678". At the bottom center is an "OK" button. At the bottom right is a checkbox labeled "Show Password" which is currently checked.

This profile shows information including:

Connect with WPS profile:

Clicking the "Connect" button will connect to AP with the selected WPS profile.

Rotate WPS profiles:

If there are more than two WPS profiles, clicking the "Rotate" button will rotate to next profile and connect to AP with this profile. If the connection can't be established successfully, station will perform the WPS profile rotation repeatedly.


Disconnect from WPS AP:

Click the "Disconnect" button to stop the WPS connection.

Delete WPS profile:

Click the "Delete" button to delete the selected WPS profile.


AP mode management guide

This adapter can be configured as AP mode. To function this adapter as an AP, please right click the  icon on system tray and select **Switch to AP mode**. Please refer to the following introduction to information about this AP-mode utility.

Note: In windows XP, it provides WPA support at hotfix Q815485 However; you have to make sure that hotfix Q815485 (require XP SP1 installed) has been installed in your system before you can start using WPA features. You can check the installation of hotfix in add/remove software page under control panel.

Config

This page provides overall configuration to this adapter. Please find the following items for identification to each field.



The screenshot shows the 'Config' tab of the AP mode management utility. The window has a menu bar with 'Config', 'Access Control', 'Mac Table', 'Event Log', 'Statistics', and 'About'. The configuration fields are as follows:

- 1: SSID text box containing 'SoftAP-13'.
- 2: Wireless Mode dropdown menu showing '802.11 B/G/N mix'.
- 3: Country Region Code dropdown menu showing '11 B/G' and '0: CH1-11'.
- 4: Wireless Protection dropdown menu showing 'Auto'.
- 5: Beacon (ms) text box containing '100'.
- 6: TX Power dropdown menu showing '100 %'.
- 7: Idle time(60 - 3600)(s) text box containing '300'.
- 8: Empty text box.
- 9: Channel dropdown menu showing '1'.
- 10: '< - Use Mac Address' button.
- 11: 'Security Setting' button.
- 12: 'No forwarding among wireless clients' checkbox (unchecked).
- 13: 'Hide SSID' checkbox (unchecked).
- 14: 'Allow B/W 40 MHz' checkbox (checked).
- 15: 'Default' button.
- 16: 'Apply' button.

A 'Help' button is located at the bottom right of the window.

1. **SSID:** AP name of user type. User also can select [Use Mac Address] to display it.
2. **Wireless Mode:** Select wireless mode. 802.11 B/G mix, 802.11B only, 802.11A only, 802.11G only, 802.11 B/G/N mix and 802.11 A/N mix mode are supported. When wireless card is 802.11N, system default is 802.11 B/G/N mix; Otherwise system default is 802.11 B/G mix (802.11 B/G/N mix selection item only exists for B/G/N adapter).

3. **Country Region Code:** eight countries to choose. Country channel list:

Classification	Range
0: FCC (Canada)	CH1 ~ CH11
1: ETSI	CH1 ~ CH13
2: SPAIN	CH10 ~ CH11
3: FRANCE	CH10 ~ CH13
4: MKK	CH14 ~ CH14
5: MKKI (TELEC)	CH1 ~ CH14
6: ISRAEL	CH3 ~ CH9
7: ISRAEL	CH5 ~ CH13

4. **Wireless Protection:** Auto, on, and off. System default is auto.
 - a. Auto: STA will dynamically change as AP announcement.
 - b. On: Always send frame with protection.
 - c. Off: Always send frame without protection.
5. **Beacon (ms):** The time between two beacons. System default is 100 ms.
6. **TX Power:** Manually force the AP transmits power. System default is 100%.
7. **TX Rate:** Manually force the Transmit using selected rate. Default is auto.
8. **Idle Time:** Manually force the Idle Time using selected value. Default is 300.
9. **Channel:** Manually force the AP using the channel. System default is channel 1.
10. **Use Mac Address:** Use MAC address of used wireless card to be AP name. System default is APX (X is last number of Mac Address).
11. **Security Setting:** Authentication mode and encryption algorithm used within the AP. System default is no authentication and encryption.
12. **No forwarding among wireless clients:** No beacon among wireless client, clients can share information each other. System default is no forwarding.
13. **Hide SSID:** Prevent this AP from recognized in wireless network. This is disabled as default.
14. **Allow BW40 MHz:** Allow BW40 MHz capability.
15. **Default:** Use system default value.
16. **Apply:** Apply the above changes.

Security Setting

This page pops up after clicking the **Security Settings** button. Please follow the instructions below:

The screenshot shows a 'Security Setting' dialog box with the following fields and options:

- 1 Authentication Type:** A dropdown menu set to 'Open'.
- 2 Encryption Type:** A dropdown menu set to 'Not Use'.
- 3 WPA Pre-shared-Key:** A text input field.
- 4 Group Rekey Interval:** A text input field containing '60 10 seconds'.
- 5 Wep Key:** A sub-dialog box containing four radio buttons labeled 'Key#1', 'Key#2', 'Key#3', and 'Key#4'. Each radio button is followed by a 'Hexa' dropdown menu and a text input field.

At the bottom of the dialog are 'OK' and 'Cancel' buttons.

Items	Information
1. Authentication Type	Select to be open or WPA-PSK system.
2. Encryption Type	Select an encryption type from the drop list.
3. WPA Pre-shared Key	A shared string between AP and STA. For WPA-PSK authentication mode, this field must be filled with character longer than 8 and less than 32 length. (PCI only)
4. Group Rekey Interval	Only valid when using WPA-PSK encryption algorithm. The key will change compliance with seconds or beacon that user set. (PCI device only)
5. WEP Key	Only valid when using WEP encryption algorithm. The key must match the key on AP. There are several formats to enter the keys. a. Hexadecimal (40bits): 10 Hex characters. b. Hexadecimal (128bits): 32Hex characters. c. ASCII (40bits): 5 ASCII characters. d. ASCII (128bits): 13 ASCII characters.

Access Control

This function filters users to use this device by designating MAC address. Please refer to the following chart for introduction.

The screenshot shows a web-based configuration interface for 'Access Control'. At the top, there are tabs: 'Config', 'Access Control' (selected), 'Mac Table', 'Event Log', 'Statistics', and 'About'. The main area contains several elements:

- 1. Access Policy:** A dropdown menu currently set to 'Disable'.
- 2. MAC Address:** A text input field for entering a MAC address, with an 'Add' button below it.
- 3. Access List:** A large empty rectangular box for displaying the list of MAC addresses.
- 4. Delete:** A button located below the 'Add' button.
- 5. Remove All:** A button located below the 'Delete' button.
- 6. Apply:** A button located at the bottom right of the configuration area.

Items	Information
1. Access Policy	Choose a method to process access control from the drop list to determine the MAC addresses that you designated are allowed to access the AP or not.
2. MAC Address	Add allowed (or denied) MAC addresses to the MAC address list.
3. Access List	Display all Mac Addresses that you designated.
4. Delete	Delete Mac addresses that you selected.
5. Remove All	Remove all Mac address in [Access List].
6. Apply	Apply changes.

MAC Table

This page displays the station detail information of current connection.

[illegible]

Items	Information
MAC Address	The station MAC address of current connection.
AID	Raise value by current connection.
Power Saving Mode	Check if the connected station supports power saving.

Event Log

Record Soft AP all event time and message.

[illegible]

Items	Information
Event Time (yy/mm/dd-hh:mm:ss)	Record event time.
Message	All event messages.

Statistics

Statistics page displays the detail counter information based on 802.11 MIB counters.

The screenshot shows a web interface with a navigation bar at the top containing tabs: Config, Access Control, Mac Table, Event Log, Statistics (selected), and About. Below the navigation bar, there are two main sections. The first section, labeled '1' in a blue circle, is titled 'Transmit Statistics' and contains a table with five rows of statistics. The second section, labeled '2' in a blue circle, is titled 'Receive Statistics' and contains a table with four rows of statistics. To the right of these sections, there is a button labeled '3' in a blue circle, which says 'RESET COUNTERS'.

Transmit Statistics		
Frames Transmitted Successfully	=	14
Frames Fail To Receive ACK After All Retries	=	0
RTS Frames Successfully Receive CTS	=	0
RTS Frames Fail To Receive CTS	=	0
Frames Transmitted Successfully After Retry	=	0

Receive Statistics		
Frames Received Successfully	=	0
Frames Received With CRC Error	=	2108
Frames Dropped Due To Out-of-Resource	=	0
Duplicate Frames Received	=	0

RESET COUNTERS

1. Transmit Statistics

Items	Information
Frames Transmitted Successfully	Frames that successfully sent.
Frames Fail To Receive ACK After All Retries	Frames that failed to transmit after hitting retry limit.
RTS Frames Successfully Receive CTS	Counts of CTS that successfully received after sending RTS frame.
RTS Frames Fail To Receive CTS	Counts of CTS that fail to be received after sending RTS frame.
Frames Retransmitted Successfully	Successfully retransmitted frames numbers.

2. Recieve Statistics

Items	Information
Frames Received Successfully	Frames received successfully.
Frames Received With CRC Error	Frames received with CRC error.
Frames Dropped Due To Out-of-Resource	Frames dropped due to resource issue.
Duplicate Frames Received	Duplicate received frames.

3. Reset Counters: Reset counters to zero.

Product Specification

Standard

IEEE 802.11n draft 2.0, IEEE 802.11b, IEEE 802.11g

Interface

PCI 2.3 or Mini PCI type III

Antenna

Antenna gain: 2dB

Antenna type: Dipole

Antenna connector type: Reverse SMA

LED indication

Link/Act (Green)

Security

64/128-bit WEP, WPA, WPA2

Receiver Sensitivity

802.11b-88dBm, 802.11g-75dBm, 802.11n-65dBm

Channel

USA 11, Europe 13

Transmit Power

802.11b 18dBm, 802.11g 15dBm, 802.11n 20MHz and 802.11n 40MHz 18dBm

Network Data Rate

802.11b: 1,2,5.5 and 11Mbps

802.11g: 6,9,12,18,24,36,48 and 54Mbps

802.11n: up to 300Mbps

Range Coverage

Indoor 35~100 meters

Outdoor 100~300 meters

Operating Temperature

0- 40 (32 – 104)

Operating Humidity

10% ~ 90% (non-condensing)

Emission

FCC Class B, CE

FCC Part 15.247 for US (2.142~2.462 MHz)

ETS 300 328 for Europe (2.400~2483.5 MHz)

DGT LP0002 for Taiwan (2.412~2.462MHz)